



ENERGY MANAGEMENT AND AUDIT - CEM REFRESHER TRAINING COURSE

KRISHNAJI PAWAR, LEED AP BD+C, GSAS CGP, ISO 14001:2015, GCP
CEM REFRESHER TRAINING COURSE





THE NEED FOR ENERGY MANAGEMENT FOR ENERGY PROFESSIONALS

KRISHNAJI PAWAR, LEED AP BD+C, GSAS CGP, ISO 14001:2015, GCP
ENERGY SPECIALIST CURRICULUM COURSE



WHAT SHOULD YOU LEARN



- Why Energy Management is Important and basics
- Global trends on Energy, Economy and Our Environment
- Non-Technical Drivers that Create the Need for Energy Projects
- Driving Factors in Major Investments For Business and Industry



THREE MAJOR PROBLEMS

Three global priorities dictate saving energy:

1. Energy Security - Reduce oil imports and balance of payments
2. Economic Competitiveness - Reduce costs and create jobs
3. Environmental Quality - Reduce global warming and acid rain

None of these goals can be fully attained without an energy efficient economy



PROFESSIONAL INTEREST ENERGY MANAGEMENT JOBS

- ☐ Building/facility/plant energy manager
- ☐ Building/facility/plant maintenance manager
- ☐ Utility energy auditor/energy analyst
- ☐ Regional/national agency energy analyst
- ☐ Consulting energy auditor and analyst
- ☐ ESCO energy auditor and analyst



TQM & ENERGY MANAGEMENT

Total Quality Management (TQM) - an integrated approach to operating a facility

-Energy cost control should be part of overall TQM program. Also CI, Six Sigma, Lean.

TQM - based on principle that front-line employees should have authority to make changes and other decisions at the lowest operating levels of a facility.

Energy management is a natural part of TQM; employees should have some training in energy management so that they can make correct energy decisions.





-

-
- | Light Source | Approximate Luminance Range (Day W/m²) |
|--------------------------|--|
| Top Incandescent (1000W) | 10 - 25 |
| Incandescent | 15 - 35 |
| Halogen | 20 - 40 |
| Halogen - Spot | 25 - 45 |
| Fluorescent | 30 - 75 |
| Fluorescent (5000K) | 35 - 80 |
| Fluorescent (4000K) | 40 - 90 |
| Daylight (1000K) | 45 - 100 |
| Daylight (5000K) | 50 - 110 |
| Daylight (4000K) | 55 - 120 |
| Daylight (3000K) | 60 - 130 |
| Daylight (2000K) | 65 - 140 |
| Daylight (1000K) | 70 - 150 |
| Daylight (5000K) | 75 - 160 |
| Daylight (4000K) | 80 - 170 |
| Daylight (3000K) | 85 - 175 |
| Daylight (2000K) | 90 - 180 |
| Daylight (1000K) | 95 - 185 |
| Daylight (5000K) | 100 - 190 |
| Daylight (4000K) | 105 - 195 |
| Daylight (3000K) | 110 - 200 |
| Daylight (2000K) | 115 - 205 |
| Daylight (1000K) | 120 - 210 |
| Daylight (5000K) | 125 - 215 |
| Daylight (4000K) | 130 - 220 |
| Daylight (3000K) | 135 - 225 |
| Daylight (2000K) | 140 - 230 |
| Daylight (1000K) | 145 - 235 |
| Daylight (5000K) | 150 - 240 |
| Daylight (4000K) | 155 - 245 |
| Daylight (3000K) | 160 - 250 |
| Daylight (2000K) | 165 - 255 |
| Daylight (1000K) | 170 - 260 |
| Daylight (5000K) | 175 - 265 |
| Daylight (4000K) | 180 - 270 |
| Daylight (3000K) | 185 - 275 |
| Daylight (2000K) | 190 - 280 |
| Daylight (1000K) | 195 - 285 |
| Daylight (5000K) | 200 - 290 |
| Daylight (4000K) | 205 - 295 |
| Daylight (3000K) | 210 - 300 |
| Daylight (2000K) | 215 - 305 |
| Daylight (1000K) | 220 - 310 |
| Daylight (5000K) | 225 - 315 |
| Daylight (4000K) | 230 - 320 |
| Daylight (3000K) | 235 - 325 |
| Daylight (2000K) | 240 - 330 |
| Daylight (1000K) | 245 - 335 |
| Daylight (5000K) | 250 - 340 |
| Daylight (4000K) | 255 - 345 |
| Daylight (3000K) | 260 - 350 |
| Daylight (2000K) | 265 - 355 |
| Daylight (1000K) | 270 - 360 |
| Daylight (5000K) | 275 - 365 |
| Daylight (4000K) | 280 - 370 |
| Daylight (3000K) | 285 - 375 |
| Daylight (2000K) | 290 - 380 |
| Daylight (1000K) | 295 - 385 |
| Daylight (5000K) | 300 - 390 |
| Daylight (4000K) | 305 - 395 |
| Daylight (3000K) | 310 - 400 |
| Daylight (2000K) | 315 - 405 |
| Daylight (1000K) | 320 - 410 |
| Daylight (5000K) | 325 - 415 |
| Daylight (4000K) | 330 - 420 |
| Daylight (3000K) | 335 - 425 |
| Daylight (2000K) | 340 - 430 |
| Daylight (1000K) | 345 - 435 |
| Daylight (5000K) | 350 - 440 |
| Daylight (4000K) | 355 - 445 |
| Daylight (3000K) | 360 - 450 |
| Daylight (2000K) | 365 - 455 |
| Daylight (1000K) | 370 - 460 |
| Daylight (5000K) | 375 - 465 |
| Daylight (4000K) | 380 - 470 |
| Daylight (3000K) | 385 - 475 |
| Daylight (2000K) | 390 - 480 |
| Daylight (1000K) | 395 - 485 |
| Daylight (5000K) | 400 - 490 |
| Daylight (4000K) | 405 - 495 |
| Daylight (3000K) | 410 - 500 |
| Daylight (2000K) | 415 - 505 |
| Daylight (1000K) | 420 - 510 |
| Daylight (5000K) | 425 - 515 |
| Daylight (4000K) | 430 - 520 |
| Daylight (3000K) | 435 - 525 |
| Daylight (2000K) | 440 - 530 |
| Daylight (1000K) | 445 - 535 |
| Daylight (5000K) | 450 - 540 |
| Daylight (4000K) | 455 - 545 |
| Daylight (3000K) | 460 - 550 |
| Daylight (2000K) | 465 - 555 |
| Daylight (1000K) | 470 - 560 |
| Daylight (5000K) | 475 - 565 |
| Daylight (4000K) | 480 - 570 |
| Daylight (3000K) | 485 - 575 |
| Daylight (2000K) | 490 - 580 |
| Daylight (1000K) | 495 - 585 |
| Daylight (5000K) | 500 - 590 |
| Daylight (4000K) | 505 - 595 |
| Daylight (3000K) | 510 - 600 |
| Daylight (2000K) | 515 - 605 |
| Daylight (1000K) | 520 - 610 |
| Daylight (5000K) | 525 - 615 |
| Daylight (4000K) | 530 - 620 |
| Daylight (3000K) | 535 - 625 |
| Daylight (2000K) | 540 - 630 |
| Daylight (1000K) | 545 - 635 |
| Daylight (5000K) | 550 - 640 |
| Daylight (4000K) | 555 - 645 |
| Daylight (3000K) | 560 - 650 |
| Daylight (2000K) | 565 - 655 |
| Daylight (1000K) | 570 - 660 |
| Daylight (5000K) | 575 - 665 |
| Daylight (4000K) | |



USA FEDERAL ENERGY EFFICIENCY REQUIREMENTS



DOE Releases Energy-Saving Rules for Federal Buildings and Proposes New Standards for Consumer Appliances

Federal Building Energy Code Requirements and Residential Appliance Proposals Would Save Americans Millions in Energy Costs and Advance Carbon Reduction Efforts. Biden Administration to Finalize 100 Actions to Save Households \$100 Annually.

Beginning in April 2023, all new buildings and major retrofits constructed by the Federal government must comply with the 2021 International Energy Conservation Code (IECC) and the 2019 American Society of Heating, Refrigerating, and Air Conditioning Engineers Standard 90.1 building energy codes. DOE estimates that this measure will save \$4.2 million dollars in operating costs within the first year of implementation.



ENERGY INTENSITY OF COUNTRIES & REGIONS



Global energy intensity improvement in 2021 is below the 2000-2019 average (-1%, vs. +1.5%/year over 2000-2019).

China's energy intensity remained stable in 2020 (-0.1%, compared to a 2.8%/year improvement over the 2000-2019 period). In 2021, its energy intensity went back to the 2000-2019 average with an improvement of 2.7%.

In 2021, energy intensity improved in Asia (especially in India and China), in Australia, in the Middle East, and in Latin America (improvements in Argentina, Chile, Colombia and Mexico).

New energy efficiency improvement in India in 2021, above the 2% average of the 2000-2019 period.

CEM EXAM FORMULAS



• GEOMETRY

- Area of circle = $\pi * r^2$
- Circumference of circle = $\pi * D$
- Area of rectangle = $L * W$
- Perimeter of rectangle = $2*L + 2*W$

• ELECTRICAL

- $V = I * R$ Ohm's Law (single phase)
- $P = I^2 * R$ Ohm's law for power (single phase)
- $kW = (V * A * 1.73 * PF) / 1000$ (3 phase) $PF = \cos \phi$
- $kW = kVA * PF$ $PF = \cos \phi$
- $kVA = 1.73 * kV * A$ (3 phase)

• MOTORS

- Percent load = $(NLRPM - RPM) / (NLRPM - FLRPM)$
- Synchronous speed = $(frequency * 60) / (number of pole pairs)$
- $kW * Percent\ load = (V * A * 1.73 * PF * Efficiency) / (3\ phase)$
- $PF = kW / kVA = \cos \phi$

• FANS AND FAN LAWS

- $LPSn / LPSo = (RPMn / RPMo)^3$ $n = new; o = old$
- $SPn / SPo = (RPMn / RPMo)^2$
- $kWn / kWo = (RPMn / RPMo)^3$
- $RPM - driven * diameter - driven = RPM - driver * diameter - driver$

- Percent OA = $(RAT - MAT) / (RAT - OAT)$

CEM EXAM FORMULAS



- **LIGHTING**
 - $RCR = (2.5 \times \text{cavity height} \times \text{perimeter}) / (\text{area})$ General
 - $RCR = (5 \times \text{height} \times (L + W)) / (L \times W)$ Rectangular room
 - Number of lamps = $(\text{LUX desired} \times \text{area}) / (\text{Lumens-per-lamp} \times \text{Cu} \times \text{L1} \times \text{L2})$
 - $\text{Lux} = \text{Lumens/d}^2$
 - Efficacy = Lumens/watt
- **HEAT FLOW**
 - $q = u \times A \times \Delta t$ W
 - $q = M \times Cp \times \Delta T$ W sensible heat only
 - $q = M \times \Delta h$ W sensible and latent heat
 - Q cooling = $U \times A \times 24 \times \text{CDD}$ Wh/yr
 - Q heating = $U \times A \times 24 \times \text{HDD}$ Wh/yr
- **MISCELLANEOUS**
 - $q = \text{LPS} \times 1.2 \times \Delta T$ W (sensible heat for air)
 - $q = \text{LPS} \times 4.2 \times \Delta t$ kW (sensible heat for water)
 - POU energy cost = $(\text{output/efficiency}) \times (\text{cost per unit})$
 - Density of dry air at standard conditions 1.204 kg/m³
 - Specific heat of dry air at standard conditions 1.006 kJ/kg°C
 - Density of water at standard conditions 1 kg/L
 - Specific heat of water at standard conditions 4.2 kJ/kg°C
 - Density of water 1000 kg/m³

BEYOND
SMART CITIES

THANK YOU

www.beyondsmartcities.in

**THE WORLD'S 1ST GREEN TECHNOLOGY
MARKETPLACE**